

WHEEL LOADER TELESCOPIC LOADER



PRODUCT RANGE 2010/I



Schaffer
Lader

Contents:

Wheel loader	2020	3
	2024	4
	2027	5
	2030	6
	2033	7
	2336	8
	2345	9
	2436/2445	10
	3350	11
	3360	12
	3450/3460	13
	4350/4360	14
	4350Z/4360Z	15
	5058Z/5058ZS	16
	5370Z/5390Z	17
9300Z/9330Z	18	
Telescopic loader	460T/470T	19
	6370T/6390T	20
	9310T	21
	9330T	22
	9380T	23
Attachements		24-32
Importers		33-34

Schäffer Lader

2020

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 14,7 kW = 20 hp
Tyres:	7.00-12 AS
Width:	790 mm – 1.150 mm
Height with ROPS-bar/folded:	2.170 mm/1.735 mm
Height with protection roof:	2.110 mm
Lifting height:	2.470 mm
Length incl. bucket:	3.330 mm
Turning radius:	530 mm
Operating weight:	1.400 kg
Lifting capacity:	1.200 kg
Tipping load, straight:	750 kg
Tipping load, articulated:	350 kg
Speed:	0 – 12 km/h



As standard:

Hydraulic four wheel drive via double gear pump, foot pedal control, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, foldable ROPS bar.

2024

Schäffer Lader

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm – 1.240 mm
Height with ROPS-bar/folded:	2.200 mm/1.770 mm
Height with protection roof:	2.200 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.500 kg
Lifting capacity:	1.400 kg
Tipping load, straight:	850 kg
Tipping load, articulated:	480 kg
Speed:	0 – 12 km/h



As standard:

Hydraulic four wheel drive via double gear pump, foot pedal control, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, foldable ROPS bar.

Schäffer Lader

2027

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm – 1.240 mm
Height with ROPS-bar/folded:	2.200 mm/1.770 mm
Height with protection roof:	2.200 mm
Lifting height:	2.800 mm/3.060 mm *
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.600 kg
Lifting capacity:	1.500 kg
Tipping load, straight:	890 kg
Tipping load, articulated:	500 kg
Speed:	0 – 15 km/h
* high lift version	



As standard:

Hydrostatic four wheel drive, foot pedal control, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, foldable ROPS bar.

2030

Schäffer Lader

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 22 kW = 30 hp
Tyres:	7.00-12 AS
Width:	890 mm – 1.240 mm
Height with ROPS-bar/folded:	2.200 mm/1.770 mm
Height with protection roof:	2.200 mm
Lifting height:	2.800 mm/3.060 mm *
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.750 kg
Lifting capacity:	1.500 kg
Tipping load, straight:	920 kg
Tipping load, articulated:	550 kg
Speed:	0 – 15 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, foldable ROPS bar.

Schäffer Lader

2033

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 24 kW = 33 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm – 1.290 mm
Height with ROPS-bar/folded:	2.310 mm/1.875 mm
Height with protection roof:	2.220 mm
Height with cab:	2.150 mm
Lifting height:	2.880 mm/3.110 mm*
Length incl. bucket:	3.610 mm
Turning radius:	580 mm
Operating weight:	1.880 kg/cab 2.080 kg
Lifting capacity:	1.600 kg
Tipping load, straight:	1.000 kg
Tipping load, articulated:	720 kg
Speed:	0 – 15 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature warning light, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, foldable ROPS bar.

2336

Schäffer Lader

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm – 1.390 mm
Height with ROPS-bar/folded:	2.280 mm/1.780 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	2.880 mm/3.110 mm*
Length incl. bucket:	3.800 mm
Turning radius:	800 mm
Operating weight:	2.200 kg/cab 2.400 kg
Lifting capacity:	1.700 kg
Tipping load, straight:	1.200 kg
Tipping load, articulated:	900 kg
Speed:	0 – 20 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature warning light, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, rear weight plate, foldable ROPS bar.

Schäffer Lader

2345

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo diesel engine 33 kW = 45 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm – 1.390 mm
Height with ROPS-bar/folded:	2.280 mm/1.780 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	2.880 mm/3.110 mm*
Length incl. bucket:	3.800 mm
Turning radius:	800 mm
Operating weight:	2.200 kg/cab 2.400 kg
Lifting capacity:	1.700 kg
Tipping load, straight:	1.300 kg
Tipping load, articulated:	930 kg
Speed:	0 – 20 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature warning light, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, rear weight plate, foldable ROPS bar.

2436/2445

Schäffer Lader

Technical Specifications:

Engine:	2436	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
	2445	4-cyl.-watercooled Kubota turbo diesel engine 33 kW = 45 hp
Tyres:		10.075-15.3 AS
Width:		1.020 mm – 1.390 mm
Height with ROPS-bar/folded:		2.280 mm/1.780 mm
Height with protection roof:		2.215 mm
Height with cab:		2.110 mm
Lifting height:		2.500 mm
Length incl. bucket:		3.800 mm
Turning radius:		800 mm
Operating weight:		2.200 kg/cab 2.400 kg
Lifting capacity:		1.900 kg
Tipping load, straight:		1.600 kg
Tipping load, articulated:		1.200 kg
Speed:		0 – 20 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature warning light, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, case weight 100 kg, low boom pivot, rear weight plate, foldable ROPS bar.

Schäffer Lader

3350

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm -1.540 mm
Height with ROPS-bar/folded:	2.360 mm /1.820 mm
Height with protection roof:	2.240 mm
Height with cab:	2.200 mm
Lifting height:	2.950 mm /3.200 mm *
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.700 kg / cab 2.900 kg
Lifting capacity:	2.000 kg
Tipping load, straight:	1.800 kg
Tipping load, articulated:	1.400 kg
Speed:	0 – 20 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, case weight 150 kg, rear weight plate, foldable ROPS bar.

3360

Schäffer Lader

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm -1.540 mm
Height with ROPS-bar/folded:	2.360 mm /1.820 mm
Height with protection roof:	2.240 mm
Height with cab:	2.200 mm
Lifting height:	2.950 mm /3.200 mm *
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.700 kg / cab 2.900 kg
Lifting capacity:	2.000 kg
Tipping load, straight:	1.800 kg
Tipping load, articulated:	1.400 kg
Speed:	0 – 20 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, case weight 150 kg, rear weight plate, foldable ROPS bar.

Schäffer Lader

3450/3460

Technical Specifications:

Engine:	3450	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	3460	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		10.075-15.3 AS
Width:		1.020 mm -1.540 mm (1.230 mm -1.600 mm with planetary axle)
Height with ROPS-bar/folded:		2.360 mm /1.820 mm
Height with protection roof:		2.240 mm
Height with cab:		2.200 mm
Lifting height:		2.600 mm
Length incl. bucket:		4.400 mm
Turning radius:		1.100 mm
Operating weight:		2.700 kg / cab 2.900 kg
Lifting capacity:		2.100 kg
Tipping load, straight:		1.950 kg
Tipping load, articulated:		1.600 kg
Speed:		0 – 20 km/h
Option:		0 – 30 km/h (type 3460)



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, low boom pivot, 20 km/h gear switchable under load, hydraulic quick-hitch, case weight 150 kg, rear weight plate, foldable ROPS bar.

4350/4360

Schäffer Lader

Technical Specifications:

Engine:	4350	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	4360	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		11.5/80-15.3 AS
Width:		1.230 mm – 1.600 mm
Height with ROPS-bar/folded:		2.360 mm /1.820 mm
Height with protection roof:		2.270 mm
Height with cab:		2.220 mm
Lifting height:		3.250 mm
Length incl. bucket:		4.500 mm
Turning radius:		1.310 mm
Operatong weight:		3.100 kg / cab 3.300 kg
Lifting capacity:		2.300 kg
Tipping load, straight:		2.000 kg
Tipping load, articulated:		1.500 kg
Speed:		0 – 20 km/h
Option:		0 – 30 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, planetary axles with automatic limited slip brakes, rear weight plate, foldable ROPS bar.

Schäffer Lader

4350Z/4360Z

Technical Specifications:

Engine:	4350Z	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	4360Z	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		11.5/80-15.3 AS
Width:		1.230 mm – 1.600 mm
Height with ROPS-bar/folded:		2.360 mm /1.820 mm
Height with protection roof:		2.270 mm
Height with cab:		2.220 mm
Lifting height:		3.260 mm
Length incl. bucket:		4.730 mm
Turning radius:		1.450 mm
Operating weight:		3.400 kg / cab 3.520 kg
Lifting capacity:		2.400 kg
Tipping load, straight:		2.200 kg
Tipping load, articulated:		1.700 kg
Speed:		0 – 20 km/h
Option:		0 – 30 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, armrest, rear weight plate, foldable ROPS bar, Z-bar linkage with parallel lift.

5058Z/5058ZS

Schäffer
Lader

Technical Specifications:

Engine:	5058Z	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
	5058ZS	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
Tyres:		15.0/55-17 AS
Width:		1.420 mm – 1.800 mm
Height with ROPS-bar/folded:		2.645 mm /2.120 mm
Height with canopy/cab:		2.320 mm
Lifting height:		3.400 mm
Length incl. bucket:		4.870 mm
Turning radius:		1.670 mm
Operating weight:		3.920 kg / cab 4.070 kg
Lifting capacity:		2.800 kg
Tipping load, straight:		2.400 kg
Tipping load, articulated:		2.100 kg
Speed:		0 – 20 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, case weight 240 kg, rear weight plate, foldable ROPS bar, Z-bar linkage with parallel lift.

Schäffer Lader

5370Z/5390Z

Technical Specifications:

Engine:	5370Z	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
	5390Z	4-cyl.-watercooled Kubota turbo diesel engine 63 kW = 86 hp
Tyres:		15.0/55-17 AS
Width:		1.420 mm – 1.800 mm
Height with canopy/cab:		2.320 mm
Lifting height:		3.400 mm
Length incl. bucket:		5.250 mm
Turning radius:		1.670 mm
Operating weight:	5370Z	4.150 kg/cab 4.300 kg
	5390Z	4.520 kg/cab 4.670 kg
Lifting capacity:		2.800 kg
Tipping load, straight:		2.600 kg/2.750 kg
Tipping load, articulated:		2.250 kg/2.400 kg
Speed:		0 – 20 km/h
Option:		0 – 30 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, (case weight 290 kg type 5390Z) rear weight plate, canopy or cab, Z-bar linkage with parallel lift.

9300Z/9330Z

Schäffer Lader

Technical Specifications:

Engine:	9300Z	4-cyl.-watercooled Deutz turbo diesel engine 81 kW = 110 hp
	9330Z	4-cyl.-watercooled Deutz intercooler turbo diesel engine 96 kW = 130 hp
Tyres:	9300Z	405/70-20
	9330Z	600/40-22.5
Width:	9300Z	1.800 mm – 2.080 mm
	9330Z	2.110 mm
Height with SCV-cab:		2.500 mm
Lifting height:		3.400 mm/3.800 mm *
Length incl. bucket:		5.560 mm
Turning radius:		1.650 mm/1.800 mm
Operating weight:	9300Z	5.550 kg/5.950 kg*
	9330Z	6.300 kg
Lifting capacity:		4.200 kg
Tipping load, straight:		3.800 kg/4.000 kg
Tipping load, articulated:		3.200 kg/3.400 kg
Speed:		0 – 20 km/h
Option:		0 – 35 km/h
		*high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Schäffer Lader

460T/470T

Technical Specifications:

Engine:	460T	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
	470T	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
Tyres:		15.0/55-17 AS
Width:		1.370 mm – 1.600 mm
Height with canopy/cab:		2.210 mm
Lifting height:		4.250 mm
Length incl. bucket:		4.990 mm
Turning radius:		1.410 mm
Operating weight:		3.950 kg / cab 4.150 kg
Lifting capacity:		1.950 kg
Tipping load:	460T	900 kg – 1.800 kg
	470T	1.000 kg – 1.900 kg
Speed:		0 – 20 km/h
Option:		0 – 30 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, canopy or cab, Z-bar linkage with parallel lift.

6370T/6390T

Schäffer Lader

Technical Specifications:

Engine:	6370T	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
	6390T	4-cyl.-watercooled Kubota turbo diesel engine 63 kW = 86 hp
Tyres:	6370T	15.0/55-17 AS
	6390T	425/55R17 AS
Width:		1.570 mm – 1.800 mm
Height with canopy/cab:		2.320 mm
Lifting height:		4.660 mm/5.100 mm*
Length incl. bucket:		5.580 mm
Turning radius:		1.750 mm
Operating weight:	6370T	4.670 kg / cab 4.820 kg
	6390T	4.750 kg / cab 4.900 kg
Lifting capacity:		2.800 kg
Tipping load:	6370T	1.200 kg – 2.400 kg
	6390T	1.300 kg – 2.500 kg
Speed:		0 – 20 km/h
Option:		0 – 30 km/h
		* high lift version



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, canopy or cab, Z-bar linkage with parallel lift.

Schäffer Lader

9310T

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz turbo diesel engine 81 kW = 110 hp
Tyres:	405/70-20
Width:	1.800 mm – 2.080 mm
Height with SCV-cab:	2.500 mm
Lifting height:	5.100 mm
Length incl. bucket:	6.040 mm
Turning radius:	2.050 mm
Operating weight with SCV-cab:	6.000 kg
Lifting capacity:	3.800 kg
Tipping load:	2.100 kg – 3.000 kg
Speed:	0 – 20 km/h
Option:	0 – 35 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

9330T

Schäffer Lader

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 96 kW = 130 hp
Tyres:	600/40-22.5
Width:	2.110 mm
Height with SCV-cab:	2.500 mm
Lifting height:	5.100 mm
Length incl. bucket:	6.040 mm
Turning radius:	1.990 mm
Operating weight with SCV-cab:	6.600 kg
Lifting capacity:	4.200 kg
Tipping load:	2.500 kg – 3.400 kg
Speed:	0 – 20 km/h
Option:	0 – 35 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at axle filled with water and antifreeze, case weight 410 kg, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Schäffer Lader

9380T

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 132 kW = 180 hp
Tyres:	650/55 R 26.5
Width:	2.400 mm
Height with SCV-cab:	2.850 mm
Lifting height:	6.900 mm
Length incl. bucket:	7.380 mm
Turning radius:	2.570 mm
Operating weight with SCV-cab:	12.500 kg
Lifting capacity:	4.900 kg
Tipping load:	3.500 kg – 4.400 kg
Speed:	0 – 40 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, reversing fan, 40 km/h gear switchable under load, Schäffer STS gearbox, 3 speed ranges, load sensing working hydraulics, hydraulic quickhitch, type Vplus, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, Ferro Form sliding elements, tyre at rear axle filled with water and antifreeze, rear weight plate, SCV-cab, air conditioner, boom suspension, Z-bar linkage with parallel lift.

4 IN 1 BUCKET



Width	Capacity	Weight
1,20 m	310 l	295 kg
1,30 m	330 l	310 kg
1,40 m	350 l	325 kg
1,60 m	550 l	420 kg
1,80 m	620 l	450 kg
2,10 m	750 l	500 kg
2,30 m	850 l	550 kg
2,50 m	950 l	600 kg

SOIL BUCKET WITH ANGULAR BODY



Width	Capacity	Width	Capacity
0,78 m	270 l	1,60 m	570 l
0,90 m	310 l	1,70 m	610 l
1,00 m	350 l	1,80 m	650 l
1,10 m	385 l	2,00 m	720 l
1,20 m	420 l	2,20 m	790 l
1,30 m	460 l	2,40 m	870 l
1,40 m	500 l	2,50 m	900 l

SOIL BUCKET WITH ROUND BUCKET



Width	Capacity	Width	Capacity
0,78 m	242 l	1,30 m	403 l
0,90 m	279 l	1,40 m	434 l
1,00 m	310 l	1,50 m	465 l
1,10 m	341 l	1,60 m	496 l
1,20 m	372 l		

LIGHT MATERIAL BUCKET



Width	Capacity	Width	Capacity
0,78 m	370 l	2,00 m	998 l
0,90 m	430 l	2,20 m	1100 l
1,00 m	484 l	2,40 m	1200 l
1,20 m	598 l	2,50 m	1300 l
1,30 m	634 l	2,20 m	1600 l
1,40 m	690 l	2,40 m	2000 l
1,50 m	743 l	high volume	
1,60 m	795 l	high volume	
1,80 m	898 l	2,50 m	2500 l
		high volume	

BUCKET WITH GRAB



Width	Capacity	Cylinder
0,78 m	370 l	1
0,90 m	430 l	1
1,00 m	484 l	1
1,20 m	598 l	1
1,40 m	690 l	2
1,60 m	795 l	2

MULTISHOVEL




Width	Capacity	Weight
1300	750 l	393 kg
1400	830 l	420 kg
1600	900 l	478 kg
1800	1000 l	512 kg
2000	1100 l	550 kg
2400	2800 l	1170 kg
2600	3000 l	1360 kg

MANURE FORK WITH GRAB



Width	Cylinder	Tines
0,78 m	1	5
0,90 m	1	5
1,00 m	1	6
1,20 m	1	7
1,20 m	2	7
1,40 m	2	8

MANURE FORK WITH GRAB HEAVY DUTY



Width	Tines
1,20 m	7
1,40 m	8
1,60 m	9
1,80 m	10
2,00 m	11
2,40 m	13

MANURE FORK



Width	Tines	Tine length
0,78 m	5	800 mm
0,90 m	5	800 mm
1,00 m	6	800 mm
1,20 m	7	800 mm
1,40 m	8	800 mm
1,60 m	9	800 mm
1,70 m	10	1100 mm
1,90 m	11	1100 mm
2,10 m	12	1100 mm

SILAGE BUCKET WITH GRAB



Width	Capacity	Tines	Weight
2,00 m	1600 l	9	770 kg
2,20 m	1750 l	10	810 kg
2,40 m	1900 l	10	850 kg

SILAGE BUCKET WITH GRAB XXL



Width	Capacity	Tines	Weight
2,20 m	2200 l	10	1080 kg
2,40 m	3450 l	13	1590 kg

SHEAR GRAB



Width	Capacity	Cut	Cyl.	Weight
0,95 m	600 l	94x80x75 cm	2	450 kg
1,20 m	730 l	115x80x75 cm	2	495 kg
1,40 m	870 l	136x80x75 cm	2	540 kg
1,60 m	1000 l	157x80x75 cm	2	705 kg
1,80 m	1160 l	178x80x75 cm	2	910 kg

HIGH TIP BUCKET



Width	Capacity	Weight
1,20 m	700 l	335 kg
1,40 m	820 l	360 kg
1,60 m	940 l	385 kg
1,80 m	1040 l	500 kg
2,00 m	1160 l	535 kg
2,20 m	1280 l	570 kg

DOZER BLADE



Width	Weight
1,50 m	150 kg
1,80 m	165 kg
2,00 m	335 kg
2,40 m	635 kg

SNOW BLADE



Width	Height	Working width 30° turned	Weight	Protection	Hydraulic turn
1,35 m	700 mm	1170 mm	180 kg	flapable blade	optional
1,50 m	700 mm	1300 mm	190 kg	flapable blade	optional
1,80 m	700 mm	1560 mm	205 kg	flapable blade	optional
2,00 m	650 mm	1700 mm	415 kg	flapable cutting edge	standard
2,40 m	650 mm	2000 mm	485 kg	flapable cutting edge	standard
2,80 m	650 mm	2350 mm	555 kg	flapable cutting edge	standard

MUCK BLADE



Width	Weight
1,50 m	110 kg
1,80 m	120 kg
2,10 m	130 kg

BALE GRIPPER



Width	Bale size	Weight
1,00 m	0,90 m - 1,80 m	180 kg
1,80 m	1,00 m - 1,80 m	350 kg

BIG BALE FORK



Width	Height	Tines	Weight
1,20 m	1,55 m	3	200 kg

SWEEPER



Width	Sweep roller	Oil needed	Weight
1,50 m	520 mm	20 l	220 kg
1,80 m	520 mm	20 l	245 kg
1,80 m	520 mm	40 l	276 kg
2,30 m	560 mm	40 l	301 kg

STRAW SPREADER




Width	Capacity	Width bucket edge	Weight
1,35 m	850 l	1,00 m	260 kg
1,55 m	1020 l	1,20 m	275 kg
1,75 m	1200 l	1,40 m	290 kg

BUCKET WITH MILLING HEAD



Width	Capacity
1,00 m	484 l
1,20 m	598 l
1,50 m	743 l

PALETT FORK



Width	Tine length	Weight	Capacity
1,00 m	1,00 m	165 kg	2,5 t
1,00 m	1,20 m	185 kg	2,5 t
1,20 m	1,00 m	198 kg	3,5 t
1,20 m	1,20 m	215 kg	3,5 t

BUCKET FOR CONCENTRATES



Width	Capacity	Weight
1,20 m	475 l	210 kg
1,40 m	575 l	240 kg
1,60 m	675 l	300 kg

POST HOLE DRILLER



Diameter	Oil needed	Weight
10 cm	20 l	125 kg
20 cm	20 l	140 kg
30 cm	20 l	152 kg
35 cm	20 l	164 kg
40 cm	20 l	176 kg

MOUNTED EXCAVATOR



For loader 2030 - 2033: NA 1200

Model	Weight	Width bucket	Max. reach	Max. height	Useable height	Working depth
NA 1200	240 kg	200 mm	1750 mm	1700 mm	1300 mm	1200 mm

For loader 2336 - 4360Z: NA 1700

Model	Weight	Width bucket	Max. reach	Max. height	Useable height	Working depth
NA 1700	390 kg	300 mm	2800 mm	2500 mm	1700 mm	2000 mm

For loader 5058Z - 5390Z - 6390T: NA 2300

Model	Weight	Width bucket	Max. reach	Max. height	Useable height	Working depth
NA 2300	550 kg	400 mm	2750 mm	2400 mm	1600 mm	2000 mm

DOUBLE KNIFE MOWER



Width	Oil needed	Weight
1,50 m	20 l	195 kg
1,90 m	20 l	215 kg


FEED BUCKET WITH CHAIN CONVEYOR



Model	Height	Width bucket edge	Overall width	Capacity	Weight
FD 100 KB	1200 mm	990 mm	1060 mm	780 l	260 kg
FD 120 KB	1200 mm	1190 mm	1240 mm	940 l	275 kg
FD 150 KB	1200 mm	1490 mm	1520 mm	1190 l	320 kg
FD 180 KB	1200 mm	1790 mm	1820 mm	1430 l	365 kg

Optional: Milling head and hydraulic control

ADAPTER EURO-WS



VERTI-FLAIL MOWER



Overall width	Working width	Weight	Knives
1,33 m	1,22 m	130 kg	4 on 2 rotors

FINISHING MOWER



Width	Weight
1,20 m	220 kg
1,50 m	280 kg
1,80 m	330 kg

ARENA LEVELER



Width	Weight
1,40 m	187 kg
1,60 m	214 kg
2,20 m	280 kg

Importers

Algeria

MULTREN Eurl
58, rue Mellal Mohamed
Staoueli
16000 Alger Algeria
phone/fax +213 21392272
tab_dz@yahoo.fr

Australia

Agtech International
Cameron Moir
22 Park Road
6050 MT. Lawley-Perth
phone +61 892712270
fax +61 892711280
www.schaffer-loaders.com.au
cmoir@agtech-international.com

Austria/Croatia/Slovenia

ERTL-AUER GmbH
Badeseestraße 5
4933 Wildenau
phone +43 77556677
fax +43 7755667773
www.ertl-auer.at
info@ertl-auer.at

Belgium

N. V. Heusdens Renting
Lichtenberglaan 1001
3800 St. Truiden
phone +32 11 683899
fax +32 11 683165
www.schaffer.be
info@schaffer.be

Bulgaria

Bulagro Mashini AD
Bulagro Center
Zheleznik District
6000 Stara Zagora
phone +359 42600171-4
fax +359 42600175
www.bulagro.com
stefan.hristov@bulagro.com

Canada

Schäffer Loaders Ltd.
653 Main Street North
Box 682, Morris
Manitoba ROG 1K0
phone +1 204 7462108
fax +1 204 7466806
bpi@mts.net

Czechia/Slovakia

Multos s. r. o.
K Silu 2263
39301 Pelhrimov
phone +420 565323284
fax +420 565327880
www.multos.cz
multos@iol.cz

Denmark/Sweden/Norway

Helms TMT-Centret A/S
Tavlundvej 4-6, Lind
7400 Herning
phone +45 99282930
fax +45 99282938
www.helmstmt.com
mail@helmstmt.com

Finnland

Konefarmi Oy
Kärsämäentie 47
20360 Turku
phone +358 424 90011
fax +358 243 11570
www.konefarmi.fi
konefarmi@konefarmi.fi

France

Ernest Roth Sàrl
16, Rue du Doubs
90101 Feche L'Eglise
phone +33 384363431
fax +33 384362117
www.rothsa.com.fr
loader@rothsa.com

Greece

EMIKO S. A.
111 Orfeos Str.
11855 Athen
phone +302 103485000
fax +302 103461653
smits@emiko.gr

Hungary

ERTL-AUER GmbH
Herr Robert Böhm
Badeseestr. 5
4933 Wildenau
phone +36 306115602
fax +43 7755667773
r.boehm@ertl-auer.at

Iran

Shaver Car Loader Co.
110 Dr. Beheshti Ave.
3rd floor Apt 8
Teheran, Iran
phone +98 21 884226345
fax +98 21 88412522
www.schafferloader.ir
info@schafferloader.ir

Ireland/UK

Cyril Johnston & Co. Ltd.
Ballynahinch Road
Carryduff, BT 8 8 DJ
N.-Ireland
phone +44 2890813121
fax +44 2890814220
www.cyriljohnston.co.uk
w.bell@cyriljohnston.net

Island

Jötunn-Vélar hf
Austurvegur 69
800 Selfoss
phone +354 4800400
fax +354 4824108
www.jotunn.is
jotunn@jotunn.is

Italy

F. Staudacher
Fuggerstr. 18, Via Fugger
39049 Sterzing-Vipiteno
phone +39 0472 766010
fax +39 0472 766585
www.staudacher.it
info@staudacher.it

**Lebanon/Syria/Jordan/Egypt/
Iraq/Nigeria**

Jerico Contracting & Trading Co.
Assad Badoui Bldg.
001 Main Street
Amioun, El Koura
Libanon
phone +961 3 231959
+961 3 233414
fax +961 6 951818
www.jericolb.com
jericolb@hotmail.com

Lithuania

UAB „CENTRAKO“
Taikos ave. 135
51129 Kaunas
phone +370 37310811
fax +370 37310584
www.centraiko.lt
centraiko@centraiko.lt

Luxembourg

Agri-Center S. A.
15, Op der Haart
9999 Wemperhardt
phone +352 23637501
fax +352 23637599
www.agri-center.lu
agri.center@massen.lu

Netherlands

Cees Berkhof
Barneveldsestraat 20
3927 CC Renswoude
phone +31 318572345
fax +31 318572325
www.ceesberkhof.nl
info@ceesberkhof.nl

Poland

PERKOZ Sp. z. o. o.
ul. Sikorskiego 19a
87-300 Brodnica
phone +48 564934057
fax +48 564983234
www.perkoz.com.pl
info@perkoz.com.pl

Portugal

SM Canaviais
Rui Batista
Quintada da Bela Vista, Pav. 31
Canaviais—7000-213 Evora
phone/fax +351 266761711
www.smcanaviais.pt
rui.batista@smcanaviais.pt

Romania

S. C. Farm Tech S. R. L.
Drumul Izlazului Nr. 9
Judetull Ifov.
077145 Orasul Pantelimon
phone +40 723549591
fax +40 213529308
evabelle@xnet.ro

Russia

Ekoniva Technika
ul. Kulneva 3
121170 Moskau
phone +7 095 9330031/32
fax +7 095 9330037
www.ekoniva.com
orderdesk@ekoniva.com

Spain

FONDRIGO MAQUINARIA
Avenida de Galicia, 109
33770 Vegadeo, Asturias
phone/fax +34 985634238
info@fondrigomaquinaria.com

Switzerland

Ernest Roth S A
5, fbg St-Germain
2900 Porrentruy
phone +41 32 4657070
fax +41 32 4657071
www.rothsa.ch
info@rothsa.com

**United Arab Emirates/Oman/
Saudi Arabia/Qatar/Jemen**

Alzar F. Z. E.
LOB-21, G-01
P. B. No. 17311,
J. A. F. Z., Dubai,
United Arab Emirates
phone +97 14-8814928
fax +97 14-8814929
www.alzarze.com
alzar@emirates.net.ae
info@alzarze.com



TECHNICAL DATA ARE SUBJECTS TO CHANGE.
STAND 11/2009

made by SCHÄFFER

SCHÄFFER MASCHINENFABRIK GMBH · POSTFACH 10 67 · 59591 ERWITTE
FON +49 (0)2943 9709-0 · FAX +49 (0)2943 9709-50 · WWW.SCHAEFFER-LADER.DE