

TR 8 Spring Suspension Trailer

- Ideal general purpose trailer
- High tip body for clean unloading
- Heavy duty structural steel 180mm channel chassis with 6 stud axles
- Heavy duty reinforced 4mm floor and side chime combined for extra strength
- Large capacity 8000Kg
- 3.7m x 2.15 x 0.56m (13ft x 7ft)
- Extra high sides 560mm (22")
- Lights and reflective triangles are standard, positioned inside heavy duty structural channel for protection against working environment
- Tandem H.D parabolic spring suspension for smooth working operation
- Spring suspension creates less stress on the trailer structure resulting in longer maintenance free operation
- H.D 3 stage Tipping Hyd cylinder
- Grain sides optional



Close coupled reinforcing floor supports for added floor strength



Specifications

Model	TR 1	TR 2	TR 4	TR 6	TR 8
Sides Height	325	360	560	560	560
Floor Thickness	2.5mm	3mm	4mm	4mm	4mm
Body Length	1.91	2.6m	3m	3.76m	4m
Width	1.22	1.37m	1.9m	2.15m	2.15
Loading Height	0.67	0.8m	0.95m	1m	1.09m
Lights	NO	Optional	yes	yes	yes
Brakes	NO	no	yes	yes	yes
Unladen Weight	347Kg	496kg	975kg	1464kg	2120kg
Wheel Size Standard	23 x 10.5 - 12	10/80 - 12	10/75 - 15.3	12.5/80 - 15.3	12.5/80 - 15.3
Wheel Size Optional	N/A	N/A	11.5/80 - 15.3	400/16 - 15.5	400/16 - 15.5

Due to a policy of continual improvement the company reserve the right to change price or specification without notice

FLEMING AGRI-PRODUCTS LTD Newbuildings Industrial Estate, Newbuildings , Northern Ireland BT47 2SX
 Tel: +44 (0)28 7134 2637 Fax: +44 (0)28 7134 4735 Email: info@fleming-agri.co.uk www.fleming-agri.co.uk

Tipping Trailers



TR 2 Trailer TR 4 Trailer
 TR 6 Trailer TR 8 Trailer

TR 1 Trailer

- All sides are removable
- 2.5mm Reinforced Floor and side chimes fabricated in one piece for extra strength
- Size 1.91 x 1.22 x 0.32m (6ft 3" x 4ft x 13")
- Reinforced sides and hinge points
- High tip for clean unloading
- Structural steel chassis with 23 x 10.50 x 12 Tyres as standard on 5 stud axle
- Parking Jack as standard
- 1500kg capacity
- Mesh sides optional



TR 2 Trailer

- All sides are removable
- 3mm Reinforced Floor and side chimes fabricated in one piece for extra strength
- Size 2.6 x 1.37 x 0.4m (8ft 6" x 4ft 7" x 14")
- Reinforced sides and hinge points
- High tip for clean unloading
- Structural steel chassis with 10 x 80 x 12.5 Tyres as standard on 5 stud axle
- Parking Jack as standard
- 2000kg capacity
- Mesh sides optional



TR 4

- Extra high 22" Reinforced sides with reinforced hinge points
- High tip for clean unloading with high specification ram
- Hydraulic brakes option
- Lights as standard fitted in protective channel
- Heavy duty 150mm structural steel channel chassis with 10.5 x 75 x 15.3 tyres as standard on 6 stud axle
- Slim-line draw-bar with hose and cable stand as standard
- 4000 Kg capacity

- All 4 side are removable and are fabricated in one piece (no water traps)
- 4mm Reinforced floor and side chimes fabricated in one piece for extra strength
- Pick up eye and shoe rest as standard with side mounting for rough terrain
- Hinge mechanism bushed and greased
- Size 3m x 1.9m x 0.56m (10ft x 6ft 6" x 22")
- Grain sides optional



TR 6

- Ideal general purpose trailer
- High tip body for clean unloading
- Heavy duty structural steel 180mm channel chassis with 6 stud axle
- Heavy duty reinforced 4mm floor and side chime combined for extra strength
- Large capacity 6000Kg
- 3.7m x 2.15 x 0.56m (12ft x 7ft)
- Extra high sides 560mm (22")
- Lights and reflective triangles are standard, positioned inside heavy duty structural channel for protection against working environment
- Grain sides optional



6 ton Capacity Easy to unload



High tip body with close spaced floor supports



Bushed pivot point with greasing facility for long life smooth operation

Lights as Standard



All 4 sides are removable



Pick up eye is standard with pick up shoe rest which can be removed and stored on the side of the draw-bar when operating on rough terrain



Slim-line draw-bar with hydraulic hose and cable stand to protect hoses and cables when in operation

Reinforced hinge supports

Hydraulic brakes as standard

12.5 x 80 x 15.3 tyres as standard on 6 stud axle with heavy duty 180mm structural steel channel chassis