



Flow-activated premium-size mobile hot water high pressure washer

NEPTUNE 7 FA is the optimal solution for heavy duty, industrial cleaning tasks. This new FA version adds a new level of reliability and comfort with the flow activated unloader system, where the flow of water over a flow sensor sends the start-stop impulses to the motor.

The tough and robust NEPTUNE 7 FA series combines low running costs, ease of use, low noise and high cleaning efficiency. The most effective tool for heavy duty, industrial hot water cleaning in any sector. The NEPTUNE 7 FA series features low running and maintenance costs, robustness, durability and high cleaning efficiency. Heating costs are reduced with the award-winning EcoPower boiler system with > 92% heating efficiency. Sound level is reduced and lifetime extended with the famous C3 pump and 1450 rpm motor.

PRODUCT FACTS

Flow activated machines may require additional back flow prevention means to satisfy local water authority requirements.

Model	NEPTUNE 7-63 FA
Ref. no	107146212
Description	NEPTUNE 7-63 FAX2
PRODUCT FEATURES	
AUTOMATIC STANDBY	■
CABLE REEL	■
ROBUST STEEL CHASSIS AND FRAME	■
ANTI CALC INDICATOR	■
FUEL INDICATOR AND GAUGE	■
PUMP OIL WARNING SYSTEM	■
SERVICE INDICATOR	■
ECO POWER BOILER-HIGH EFFICIENCY	■
HOSE REEL	■
SILENT POWER - 1450 RPM MOTOR	■
C3 4-CERAMIC PISTON PUMP	■
FULL CERAMIC PISTONS	■
WDK DUAL DETERGENT INJECTOR	■
QUICK SERVICE - INNOVATIVE CONCEPT	■
ERGO ACCESSORY SYSTEM	■
INCL. ACCESSORIES	
106403122 ERGO 2000 STANDARD W.HOSE	■
1402072 HOSE 20 M. BLACK 3/8in HS	■
61369 HOSE NOZZLE	■
101119496 REPAIR KIT (M.FCOUP/RESTR	■
101119747 TORNADO KIT (RING/NOZZLE	■
106403010 TORNADO PLUS 1120	■

Technical specifications	NEPTUNE 7-63 FA
EL CABLE (M)	10
POWER CONSUMPTION (KW)	8,3
VOLTAGE/PHASE/FREQUENCY/CURRENT (V/~/HZ/A)	400/3/50/15
CLEANING IMPACT (KG/FORCE)	6,3
WATER FLOW QMAX/QIEC (L/H)	1260/1170
WATER TEMPERATURE (WATER/STEAM) (°C)	90/150
PUMP PRESSURE (BAR/MPA)	175/17,5
PUMP (RPM)	1450
FUEL CONSUMPTION DT 45 °C (KG/H)	5,6
FUEL TANK (L)	35
DETERGENT TANK (L)	A: 15 + B: 10
NOZZLE SIZE	0680
MAX INLET TEMPERATURE (°C)	40
NUMBER OF PISTONS	4
CERAMIC PISTONS	x
DIMENSIONS LXWXH (MM)	1190 x 702 987
WEIGHT (KG)	224