

- ▲ Cutting depth 1.05 m.
- ▲ Enormous load capacity
- ▲ Saves time and fuel
- ▲ Capacity 3.4 m³
- ▲ Perfect in combination with Triomatic
- ▲ Designed for attachment to loaders

NEW!



Turbobuster 180 XL

feeding

mixing

loading

cutting

Turbobuster 180 XL



Standard features...

- ▲ Heavy Duty model
- ▲ Back-plates
- ▲ Protected cable housing
- ▲ Knife protectors
- ▲ Hardened knives
- ▲ Bypass-system
- ▲ Quick-detachable coupling
- ▲ Attachement plates for tractors classification 2 & 2/3
- ▲ Hydraulic push-off

Accessories...

- ▲ Attachement plates for tractors classification 3
- ▲ Universal attachment for loader
- ▲ High-lift 1.40 m
- ▲ Hydraulic top-link



Technical Data

Turbobuster 180 XL

Capacity m ³	3.40
Overall Length m	1.40
Overall length with high-lift m	1.59
Overall width m	1.97
Overall height m	2.71
Overall height with high-lift m	2.71
Net weight kg	900
Net weight with high-lift kg	1.300
Block height m	1.80
Loading capacity (Max. height) m	2.30
Loading with high-lift (Max. height) m	3.70
Block dimensions (length x width x height) m	1.05 x 1.80 x 1.80
Required hydraulic capacity min.	28 l/min., 150 bar
Required hydraulic capacity max.	65 l/min., 200 bar
Required tractor hydraulics	1 double acting valve
Minimum load capacity loader kg	3.500

Trioliet reserves the right to make changes in design and specifications, or to add new features without obligation on implements before or after such changes are made.



TRIOLIET MULLOS B.V.

Hinmanweg 19
 NL-7575 BE Oldenzaal
 The Netherlands
Tel. +31 541 57 21 21
Fax +31 541 57 21 25
E-mail info@trioliet.com
www.trioliet.com



Trioliet: Invents for you.